

## LAMPIRAN

### Index.php

```
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0
Transitional//EN" "http://www.w3.org/TR/xhtml1/DTD/xhtml1-
transitional.dtd">
<html xmlns="http://www.w3.org/1999/xhtml">
<head>
<meta http-equiv="Content-Type" content="text/html;
charset=utf-8" />
<title>Merah Hotel - Mengutamakan Kenyamanan Anda</title>

<link href="css2/templatemo_style.css" rel="stylesheet"
type="text/css" />

<link rel="stylesheet" href="css2/nivo-slider.css"
type="text/css" media="screen" />
<link rel="stylesheet" type="text/css"
href="css2/ddsmoothmenu.css" />

<script language="javascript" type="text/javascript">
function clearText(field)
{
    if (field.defaultValue == field.value) field.value = '';
    else if (field.value == '') field.value =
field.defaultValue;
}
</script>

<script type="text/javascript"
src="js2/jquery.min.js"></script>
<script type="text/javascript" src="js2/ddsmoothmenu.js">
</script>

<script type="text/javascript">

ddsmoothmenu.init({
    mainmenuid: "templatemo_menu", //menu DIV id
    orientation: 'h', //Horizontal or vertical menu: Set
to "h" or "v"
    classname: 'ddsmoothmenu', //class added to menu's
outer DIV
    //customtheme: ["#1c5a80", "#18374a"],
    contentsource: "markup" //"markup" or ["container_id",
"path_to_menu_file"]
})

</script>

<script type="text/javascript" src="js2/jquery-1-4-
2.min.js"></script>
```

```

<link rel="stylesheet" href="css2/slimbox2.css"
type="text/css" media="screen" />
<script type="text/JavaScript"
src="js2/slimbox2.js"></script>

</head>
<body>

<div id="templatemo_body_wrapper">
    <div id="templatemo_wrapper"><span
id="templatemo_wrapper_top"></span>
        <div id="templatemo_header">
            <div id="site_title"><a href="index.php">Hotel
Merah</a></div>
            <div id="templatemo_menu" class="ddsmoothmenu">
                <ul>
                    <li><a href="home.php"
class="selected">Home</a></li>
                    <li><a href="agenda.php">Agenda</a>

                    <li><a href="portfolio.php">Gallery</a>

                    </li>
                    <li><a
href="tarifhot.php">Tarif</a></li>
                    <li><a
href="admin/admin.php">Admin</a></li>
                </ul>
                <br style="clear: left" />
            </div> <!-- end of templatemo_menu -->
            <a href="http://www.vectorhq.com" title="Free
Vector Images from www.vectorhq.com"
class="templatemo_header_img" target="_blank">Back to
Homepage</a>
        </div>
        <div id="templatemo_slider">
            <div id="slider-wrapper">
                <div id="slider" class="nivoSlider">
                    
                    <a href="#"></a>
                    
                    
                </div>
            </div>
        </div>
    </div>
</div>

```

```
        
    </div>
    <div id="htmlcaption" class="nivo-html-
caption">
        <strong>This</strong> meag hotel
<em>HTML</em> caption with <a href="#">a link</a>.
    </div>
</div>
<script type="text/javascript" src="js2/jquery-
1.4.3.min.js"></script>
<script type="text/javascript"
src="js2/jquery.nivo.slider.pack.js"></script>
<script type="text/javascript">
$(window).load(function() {
    $('#slider').nivoSlider();
});
</script>
</div>
<div id="templatemo_main">
    <div class="col col23">
```

## Kamar.php

```
<?php require_once('Connections/koneksi.php'); ?>
<?php
function GetSQLValueString($theValue, $theType,
    $theDefinedValue = "", $theNotDefinedValue = "")
{
    $theValue = (!get_magic_quotes_gpc()) ?
    addslashes($theValue) : $theValue;

    switch ($theType) {
        case "text":
            $theValue = ($theValue != "") ? "'" . $theValue . "'"
: "NULL";
            break;
        case "long":
        case "int":
            $theValue = ($theValue != "") ? intval($theValue) :
"NULL";
            break;
        case "double":
            $theValue = ($theValue != "") ? "'" .
doubleval($theValue) . "'" : "NULL";
            break;
        case "date":
            $theValue = ($theValue != "") ? "'" . $theValue . "'"
: "NULL";
            break;
        case "defined":
            $theValue = ($theValue != "") ? $theDefinedValue :
$theNotDefinedValue;
            break;
    }
    return $theValue;
}

$maxRows_Recordset1 = 10;
$pageNum_Recordset1 = 0;
if (isset($_GET['pageNum_Recordset1'])) {
    $pageNum_Recordset1 = $_GET['pageNum_Recordset1'];
}
$startRow_Recordset1 = $pageNum_Recordset1 *
$maxRows_Recordset1;

mysql_select_db($database_koneksi, $koneksi);
$query_Recordset1 = "SELECT * FROM tbhargakamar";
$query_limit_Recordset1 = sprintf("%s LIMIT %d, %d",
$query_Recordset1, $startRow_Recordset1,
$maxRows_Recordset1);
$Recordset1 = mysql_query($query_limit_Recordset1, $koneksi)
or die(mysql_error());
$row_Recordset1 = mysql_fetch_assoc($Recordset1);
```

```

if (isset($_GET['totalRows_Recordset1'])) {
    $totalRows_Recordset1 = $_GET['totalRows_Recordset1'];
} else {
    $all_Recordset1 = mysql_query($query_Recordset1);
    $totalRows_Recordset1 = mysql_num_rows($all_Recordset1);
}
$totalPages_Recordset1 =
ceil($totalRows_Recordset1/$maxRows_Recordset1)-1;

mysql_select_db($database_koneksi, $koneksi);
$query_Recordset2 = "SELECT nama_event, keterangan FROM
tevent";
$Recordset2 = mysql_query($query_Recordset2, $koneksi) or
die(mysql_error());
$row_Recordset2 = mysql_fetch_assoc($Recordset2);
$totalRows_Recordset2 = mysql_num_rows($Recordset2);

mysql_select_db($database_koneksi, $koneksi);
$query_Recordset3 = "SELECT * FROM tbpesanan";
$Recordset3 = mysql_query($query_Recordset3, $koneksi) or
die(mysql_error());
$row_Recordset3 = mysql_fetch_assoc($Recordset3);
$totalRows_Recordset3 = mysql_num_rows($Recordset3);

mysql_select_db($database_koneksi, $koneksi);
$query_Recordset4 = "SELECT * FROM tbkamar";
$Recordset4 = mysql_query($query_Recordset4, $koneksi) or
die(mysql_error());
$row_Recordset4 = mysql_fetch_assoc($Recordset4);
$totalRows_Recordset4 = mysql_num_rows($Recordset4);
?>
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01
Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
<html>
<head>
<title>Untitled Document</title>
<meta http-equiv="Content-Type" content="text/html;
charset=iso-8859-1">
<link rel="stylesheet" type="text/css"
href="css/superfish.css">
<link type="text/css" href="development-
bundle/themes/base/ui.all.css" rel="stylesheet" />
<script type="text/javascript" src="js/jquery-
1.4.js"></script>
<script type="text/javascript"
src="js/hoverIntent.js"></script>
<script type="text/javascript"
src="js/superfish.js"></script>
<script type="text/javascript"
src="js/jquery.watermark.min.js"></script>

```

```

    <script type="text/javascript" src="development-
bundle/jquery-1.3.2.js"></script>
    <script type="text/javascript" src="development-
bundle/ui/ui.core.js"></script>
    <script type="text/javascript" src="development-
bundle/ui/ui.datepicker.js"></script>

    <script type="text/javascript" src="development-
bundle/ui/i18n/ui.datepicker-id.js"></script>
    <script type="text/javascript">
        $(document).ready(function() {

            $("#jenis").datepicker({
                dateFormat      : "yy-mm-dd",
                showOn          : "button",
                buttonImage     : "development-
bundle/demos/datepicker/images/calendar.gif",
                buttonImageOnly : true
            });

            $("#jenis2").datepicker({
                dateFormat      : "yy-mm-dd",
                showOn          : "button",
                buttonImage     : "development-
bundle/demos/datepicker/images/calendar.gif",
                buttonImageOnly : true
            });

            $("#jenis3").datepicker({
                dateFormat      : "yy-mm-dd",
                showOn          : "button",
                buttonImage     : "development-
bundle/demos/datepicker/images/calendar.gif",
                buttonImageOnly : true
            });

            $("#jenis").change(function(){
                var jenis = $("#jenis").val();
                $("#jenis12").val(jenis);
            });
            $("#jenis2").change(function(){
                var jenis2 = $("#jenis2").val();
                $("#jenis22").val(jenis2);
            });

            $("#kategori").change(function(){
                var kategori_kamar = $("#kategori").val();
                var checkin = $("#jenis").val();
                var checkout = $("#jenis2").val();
                $.ajax({
                    url: "proses_harga.php",

```

## Pesan.php

```
<?php require_once('Connections/koneksi.php'); ?>
<?php
function GetSQLValueString($theValue, $theType,
$theDefinedValue = "", $theNotDefinedValue = "")
{
    $theValue = (!get_magic_quotes_gpc()) ?
addslashes($theValue) : $theValue;

    switch ($theType) {
        case "text":
            $theValue = ($theValue != "") ? "'" . $theValue . "'"
: "NULL";
            break;
        case "long":
        case "int":
            $theValue = ($theValue != "") ? intval($theValue) :
"NULL";
            break;
        case "double":
            $theValue = ($theValue != "") ? "'" .
doubleval($theValue) . "'" : "NULL";
            break;
        case "date":
            $theValue = ($theValue != "") ? "'" . $theValue . "'"
: "NULL";
            break;
        case "defined":
            $theValue = ($theValue != "") ? $theDefinedValue :
$theNotDefinedValue;
            break;
    }
    return $theValue;
}

$editFormAction = $_SERVER['PHP_SELF'];
if (isset($_SERVER['QUERY_STRING'])) {
    $editFormAction .= "?" .
htmlentities($_SERVER['QUERY_STRING']);
}

if ((isset($_POST["MM_insert"])) && ($_POST["MM_insert"] ==
"form1")) {
    $insertSQL = sprintf("INSERT INTO tbpesanan (nama_pemesan,
kategori_kamar, no_kamar, harga_kamar, tgl_checkin,
tgl_checkout, tgl_pemesanan, total_harga, alamat, no_hp,
kode_acak) VALUES (%s, %s, %s, %s, %s, %s, %s, %s, %s, %s,
%s)",

    GetSQLValueString($_POST['nama_pemesan'], "text"),
```

```

GetSQLValueString($_POST['kategori_kamar'], "text"),
                    GetSQLValueString($_POST['no_kamar'],
"text"),

GetSQLValueString($_POST['harga_kamar'], "double"),

GetSQLValueString($_POST['tgl_checkin'], "text"),

GetSQLValueString($_POST['tgl_checkout'], "text"),

GetSQLValueString($_POST['tgl_pemesanan'], "text"),

GetSQLValueString($_POST['total_harga'], "double"),
                    GetSQLValueString($_POST['alamat'],
"text"),
                    GetSQLValueString($_POST['no_hp'],
"text"),

GetSQLValueString($_POST['kode_acak'], "int"));

mysql_select_db($database_koneksi, $koneksi);
$result1 = mysql_query($insertSQL, $koneksi) or
die(mysql_error());

$insertGoTo = "next2.php";
if (isset($_SERVER['QUERY_STRING'])) {
    $insertGoTo .= (strpos($insertGoTo, '?')) ? "&" : "?";
    $insertGoTo .= $_SERVER['QUERY_STRING'];
}
header(sprintf("Location: %s", $insertGoTo));
}

mysql_select_db($database_koneksi, $koneksi);
$query_Recordset1 = "SELECT * FROM tbpesanan";
$Recordset1 = mysql_query($query_Recordset1, $koneksi) or
die(mysql_error());
$row_Recordset1 = mysql_fetch_assoc($Recordset1);
$totalRows_Recordset1 = mysql_num_rows($Recordset1);
?>
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01
Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
<html>
<head>
<title>Untitled Document</title>
<meta http-equiv="Content-Type" content="text/html;
charset=iso-8859-1">
<style type="text/css">
<!--
.style1 {
    font-family: Arial, Helvetica, sans-serif;
    font-weight: bold;

```



```

        <td><input type="text" name="tgl_checkout"
value="" size="32"></td>
    </tr>
    <tr valign="baseline">
        <td nowrap align="right"><strong>Tgl
Pemesanan:</strong></td>
        <td><input type="text" name="tgl_pemesanan"
value="<?php echo date("Y-m-d"); ?>" disabled
size="32"></td>
    </tr>
    <tr valign="baseline">
        <td nowrap align="right"><strong>Total
Harga:</strong></td>
        <td><input type="text" name="total_harga" value=""
size="32"></td>
    </tr>
    <tr valign="baseline">
        <td nowrap align="right"><strong>Alamat:</strong></td>
        <td><!--<input type="text" name="alamat" value=""
size="32">-->
        <textarea name="alamat"></textarea></td>
    </tr>
    <tr valign="baseline">
        <td nowrap align="right"><strong>Nomor
Telepon:</strong></td>
        <td><input type="text" name="no_hp" value=""
size="32"></td>
    </tr>
    <tr valign="baseline">
        <td nowrap align="right">&nbsp;</td>
        <td><input type="submit" value="Pesan Sekarang"></td>
    </tr>
</table>

```

## Tarif.php

```
<?php require_once('Connections/koneksi.php'); ?>
<?php
function GetSQLValueString($theValue, $theType,
    $theDefinedValue = "", $theNotDefinedValue = "")
{
    $theValue = (!get_magic_quotes_gpc()) ?
    addslashes($theValue) : $theValue;

    switch ($theType) {
        case "text":
            $theValue = ($theValue != "") ? "'" . $theValue . "'"
: "NULL";
            break;
        case "long":
        case "int":
            $theValue = ($theValue != "") ? intval($theValue) :
"NULL";
            break;
        case "double":
            $theValue = ($theValue != "") ? "'" .
doubleval($theValue) . "'" : "NULL";
            break;
        case "date":
            $theValue = ($theValue != "") ? "'" . $theValue . "'"
: "NULL";
            break;
        case "defined":
            $theValue = ($theValue != "") ? $theDefinedValue :
$theNotDefinedValue;
            break;
    }
    return $theValue;
}

$maxRows_Recordset1 = 10;
$pageNum_Recordset1 = 0;
if (isset($_GET['pageNum_Recordset1'])) {
    $pageNum_Recordset1 = $_GET['pageNum_Recordset1'];
}
$startRow_Recordset1 = $pageNum_Recordset1 *
$maxRows_Recordset1;

mysql_select_db($database_koneksi, $koneksi);
$query_Recordset1 = "SELECT * FROM tbhargakamar";
$query_limit_Recordset1 = sprintf("%s LIMIT %d, %d",
$query_Recordset1, $startRow_Recordset1,
$maxRows_Recordset1);
$Recordset1 = mysql_query($query_limit_Recordset1, $koneksi)
or die(mysql_error());
$row_Recordset1 = mysql_fetch_assoc($Recordset1);
```

```

if (isset($_GET['totalRows_Recordset1'])) {
    $totalRows_Recordset1 = $_GET['totalRows_Recordset1'];
} else {
    $all_Recordset1 = mysql_query($query_Recordset1);
    $totalRows_Recordset1 = mysql_num_rows($all_Recordset1);
}
$totalPages_Recordset1 =
ceil($totalRows_Recordset1/$maxRows_Recordset1)-1;

mysql_select_db($database_koneksi, $koneksi);
$query_Recordset2 = "SELECT nama_event, keterangan FROM
tevent";
$Recordset2 = mysql_query($query_Recordset2, $koneksi) or
die(mysql_error());
$row_Recordset2 = mysql_fetch_assoc($Recordset2);
$totalRows_Recordset2 = mysql_num_rows($Recordset2);

mysql_select_db($database_koneksi, $koneksi);
$query_Recordset3 = "SELECT * FROM tbpesanan";
$Recordset3 = mysql_query($query_Recordset3, $koneksi) or
die(mysql_error());
$row_Recordset3 = mysql_fetch_assoc($Recordset3);
$totalRows_Recordset3 = mysql_num_rows($Recordset3);

mysql_select_db($database_koneksi, $koneksi);
$query_Recordset4 = "SELECT * FROM tbkamar";
$Recordset4 = mysql_query($query_Recordset4, $koneksi) or
die(mysql_error());
$row_Recordset4 = mysql_fetch_assoc($Recordset4);
$totalRows_Recordset4 = mysql_num_rows($Recordset4);
?>
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01
Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
<html>
<head>
<title>Untitled Document</title>
<meta http-equiv="Content-Type" content="text/html;
charset=iso-8859-1">
<link rel="stylesheet" type="text/css"
href="css/superfish.css">
<link type="text/css" href="development-
bundle/themes/base/ui.all.css" rel="stylesheet" />
<script type="text/javascript" src="js/jquery-
1.4.js"></script>
<script type="text/javascript"
src="js/hoverIntent.js"></script>
<script type="text/javascript"
src="js/superfish.js"></script>
<script type="text/javascript"
src="js/jquery.watermark.min.js"></script>

```

## Admin.php

```
<?php
//initialize the session
session_start();

// ** Logout the current user. **
$logoutAction = $_SERVER['PHP_SELF']."?doLogout=true";
if ((isset($_SERVER['QUERY_STRING'])) &&
($_SERVER['QUERY_STRING'] != "")){
    $logoutAction .="&".
htmlentities($_SERVER['QUERY_STRING']);
}

if ((isset($_GET['doLogout']))
&&($_GET['doLogout']=="true")){
    //to fully log out a visitor we need to clear the session
    variables
    session_unregister('MM_Username');
    session_unregister('MM_UserGroup');

    $logoutGoTo = "logout.php";
    if ($logoutGoTo) {
        header("Location: $logoutGoTo");
        exit;
    }
}
?>
<?php
session_start();
$MM_authorizedUsers = "";
$MM_donotCheckaccess = "true";

// *** Restrict Access To Page: Grant or deny access to this
page
function isAuthorized($strUsers, $strGroups, $UserName,
$UserGroup) {
    // For security, start by assuming the visitor is NOT
authorized.
    $isValid = False;

    // When a visitor has logged into this site, the Session
variable MM_Username set equal to their username.
    // Therefore, we know that a user is NOT logged in if that
Session variable is blank.
    if (!empty($UserName)) {
        // Besides being logged in, you may restrict access to
only certain users based on an ID established when they
login.
        // Parse the strings into arrays.
        $arrUsers = Explode(",", $strUsers);
        $arrGroups = Explode(",", $strGroups);
```

```

        if (in_array($UserName, $arrUsers)) {
            $isValid = true;
        }
        // Or, you may restrict access to only certain users
based on their username.
        if (in_array($UserGroup, $arrGroups)) {
            $isValid = true;
        }
        if (($strUsers == "") && true) {
            $isValid = true;
        }
    }
    return $isValid;
}

$MM_restrictGoTo = "admin.php";
if (!(isset($_SESSION['MM_Username'])) &&
(isAuthorized("", $MM_authorizedUsers,
$_SESSION['MM_Username'], $_SESSION['MM_UserGroup']))) {
    $MM_qsChar = "?";
    $MM_referrer = $_SERVER['PHP_SELF'];
    if (strpos($MM_restrictGoTo, "?")) $MM_qsChar = "&";
    if (isset($_QUERY_STRING) && strlen($_QUERY_STRING) > 0)
    $MM_referrer .= "?" . $_QUERY_STRING;
    $MM_restrictGoTo = $MM_restrictGoTo. $MM_qsChar .
"accesscheck=" . urlencode($MM_referrer);
    header("Location: " . $MM_restrictGoTo);
    exit;
}
?>
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01
Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
<html>
<head>
<title>Admin Panel Hotel Mustika</title>
<meta http-equiv="Content-Type" content="text/html;
charset=iso-8859-1">
<link rel="stylesheet" href="css/style2.css">
<script type="text/javascript" src="js/jquery-
1.4.min.js"></script>
<script type="text/javascript"
src="js/jquery.jqDock.min.js"></script>
<script type="text/javascript">
        $(function(){
            $('#menu').jqDock({ align: 'top', duration:
200, labels: 'br', size: 48, distance: 10, fadeIn: 2000});
        });
</script>
</head>

```

## Tambahkamar.php

```
<?php require_once('../Connections/koneksi.php'); ?>
<?php
session_start();
$MM_authorizedUsers = "";
$MM_donotCheckaccess = "true";

// *** Restrict Access To Page: Grant or deny access to this
page
function isAuthorized($strUsers, $strGroups, $UserName,
$UserGroup) {
    // For security, start by assuming the visitor is NOT
authorized.
    $isValid = False;

    // When a visitor has logged into this site, the Session
variable MM_Username set equal to their username.
    // Therefore, we know that a user is NOT logged in if that
Session variable is blank.
    if (!empty($UserName)) {
        // Besides being logged in, you may restrict access to
only certain users based on an ID established when they
login.
        // Parse the strings into arrays.
        $arrUsers = Explode(",", $strUsers);
        $arrGroups = Explode(",", $strGroups);
        if (in_array($UserName, $arrUsers)) {
            $isValid = true;
        }
        // Or, you may restrict access to only certain users
based on their username.
        if (in_array($UserGroup, $arrGroups)) {
            $isValid = true;
        }
        if (($strUsers == "") && true) {
            $isValid = true;
        }
    }
    return $isValid;
}

$MM_restrictGoTo = "admin.php";
if (!(isset($_SESSION['MM_Username']) &&
(isAuthorized("", $MM_authorizedUsers,
$_SESSION['MM_Username'], $_SESSION['MM_UserGroup'])))) {
    $MM_qsChar = "?";
    $MM_referrer = $_SERVER['PHP_SELF'];
    if (strpos($MM_restrictGoTo, "?") $MM_qsChar = "&";
    if (isset($QUERY_STRING) && strlen($QUERY_STRING) > 0)
$MM_referrer .= "?" . $QUERY_STRING;
```

```

    $MM_restrictGoTo = $MM_restrictGoTo. $MM_qsChar .
"accesscheck=" . urlencode($MM_referrer);
    header("Location: ". $MM_restrictGoTo);
    exit;
}
?>
<?php
function GetSQLValueString($theValue, $theType,
$theDefinedValue = "", $theNotDefinedValue = "")
{
    $theValue = (!get_magic_quotes_gpc()) ?
addslashes($theValue) : $theValue;

    switch ($theType) {
        case "text":
            $theValue = ($theValue != "") ? "'" . $theValue . "'"
: "NULL";
            break;
        case "long":
        case "int":
            $theValue = ($theValue != "") ? intval($theValue) :
"NULL";
            break;
        case "double":
            $theValue = ($theValue != "") ? "'" .
doubleval($theValue) . "'" : "NULL";
            break;
        case "date":
            $theValue = ($theValue != "") ? "'" . $theValue . "'"
: "NULL";
            break;
        case "defined":
            $theValue = ($theValue != "") ? $theDefinedValue :
$theNotDefinedValue;
            break;
    }
    return $theValue;
}

$editFormAction = $_SERVER['PHP_SELF'];
if (isset($_SERVER['QUERY_STRING'])) {
    $editFormAction .= "?" .
htmlentities($_SERVER['QUERY_STRING']);
}
if (isset($_POST["Kembali"])) {
    $editFormAction="datakamar.php";
    header("Location: ". $editFormAction);
} else {
    if ((isset($_POST["MM_insert"])) && ($_POST["MM_insert"] ==
"form1")) {
        $insertSQL = sprintf("INSERT INTO tbkamar (no_kamar,
kategori_kamar, status) VALUES (%s, %s, %s)",.php";

```