

Index.php

```
<html>
<head>
<script type="text/javascript">
function removeElement()
{
document.getElementById("submenu").style.display="none";
document.getElementById("submenu2").style.display="none";
document.getElementById("submenu3").style.display="none";
document.getElementById("submenu4").style.display="none";

}
function changeVisibility()
{
document.getElementById("submenu").style.visibility="hidden";
}
function resetElement()
{
document.getElementById("submenu").style.display="block";
}
function resetElement2()
{
document.getElementById("submenu2").style.display="block";
}
function resetElement3()
{
document.getElementById("submenu3").style.display="block";
}
function resetElement4()
{
document.getElementById("submenu4").style.display="block";
}

function open_win()
{
window.open("pilih.php","_top");
}
function open_winloginoperator()
{
window.open("operator/login.php","_top");
}
function open_winloginadmin()
{
window.open("login.php","_top");
}
}
</script>

<style>
#container
{
background-color:WHITE;
width:90%;
padding:5px;
border-radius:10px 10px 10px 10px;
box-shadow:0pt 3px 3px rgba(20, 20, 20, 0.5) inset;
}
.tempatmenu
{
width:100%;
height:30px;
background-color:rgb(255,204,0);
}

ul
{
list-style-type:none;
margin:0;
padding:0;
}
.list
{
margin:1px;
width:150px;
align:center;
background-image:url('image/tombol3.png');
height:28px;
opacity:0.7;
}

.menu
{
float:left;
margin:1px;
width:150px;
height:25px;
}
.header
{
height:150px;
}
#menudalam
{
align:center;
```

```

background-color:#FF6600;
height:28px;
opacity:1;
cursor:pointer;
}
#menudalam:hover {
background-color:#FFff66;
opacity:1;
}
#tengah
{
margin-top:3px;
margin-bottom:3px;
padding:0px;
}
.kiri
{
float:left;
background-color:#FF9933;
width:60%;
height:510px;
padding:5px;
}
.kanan
{
float:right;
width:35%;
height:550px;
background-color:#FF9933;
}
#submenu
{
display:none;
position:absolute;
z-index:5;
}
#submenu2
{
display:none;
position:absolute;
z-index:5;
}
#submenu3
{
display:none;
position:absolute;
z-index:5;
}
#submenu4
{
display:none;
position:absolute;

```

```

z-index:5;
}
#zonafooter
{
float:left;
width:33%;
background-color:#FF9933;
margin-bottom:10px;
}
#footer2
{
margin-bottom:10px;
width:100%;
height:100px;
}
body {
background-color: #FFFF99;
}
</style>
<meta http-equiv="Content-Type"
content="text/html; charset=iso-8859-
1"></head>
<body >
<div id="wrapper" align="center" >
<div id="container" style="margin:10px">
<div id="top" style="background-
color:#FFCC99" align="left">
<div style="float:left; margin-
top:15px; font-family: Geneva, Arial,
Helvetica, sans-serif; font-size: 18px; font-
weight: bold; color: #FF9900;">Surya Mas
Travel Magetan </div>
</div>
<!-- div top -->

<div class="header" >

</div><!-- div header -->
<div class="tempatmenu">
<div class="menu"
onMouseOver="resetElement()"
onMouseOut="removeElement()" >

```

```

        <div
id="menudalam" align="center"
onClick="open_winloginoperator()"><B>Op
erator</B>
        </div><!-- div
menudalam -->
id="submenu">
        <ul>
        <!--
<li><div class="list" align="center"
><B>User</B></div></li>
        <!--
<li><div class="list" align="center"
onClick="open_winloginoperator()"><B>Ope
rator</B></div></li> -->
        <!--
<li><div class="list" align="center"
onClick="open_winloginadmin()"><B>Admin
</B></div></li> -->
        <!--
<li><div class="list" align="center"><a
href="#about">About</a></div></li> -->
        </ul>
        </div><!-- div submenu -->
        </div><!-- div menu -->
        <div class="menu"
onMouseOver="resetElement2()"
onMouseOut="removeElement()">
        <div
id="menudalam" align="center"
onClick="open_winloginadmin()"><B>Admi
n</B>
        </div><!-- div
menudalam -->
id="submenu2">
        <ul>
        <!--
<li><div class="list" align="center"><a
href="#home"><B>Travel</B></a></div></l
i>
        <!--
class="list" align="center"><a
href="#news"><B>Jemput
Berkala</B></a></div></li>
        <!--
class="list" align="center"><a
href="#contact"><B>Sewa Travel
</B></a></div></li>

```

```

        <!--
<li><div class="list" align="center"><a
href="#about">About</a></div></li> -->
        </ul>
        </div><!-- div submenu2 -->
        </div><!-- div menu -->
        <!--
        <div class="menu"
onmouseover="resetElement3()"
onmouseout="removeElement()">
        <div
id="menudalam"
align="center"><B>Hotel</B>
        </div><!-- div
menudalam -->
id="submenu3">
        <ul>
        <li><div
class="list" align="center"><a
href="#home"><B>Hotel-hotel
Jakarta</B></a></div></li>
        <li><div
class="list" align="center"><a
href="#news"><B>Hotel-hotel
Bali</B></a></div></li>
        <li><div
class="list" align="center"><a
href="#contact"><B>Hotel-hotel
Yogya</B></a></div></li>
        <li><div
class="list" align="center"><a
href="#about"><B>Hotel-hotel
Bandung</B></a></div></li>
        </ul>
        </div><!-- div submenu3 -->
        </div><!-- div menu -->
        <!--
        <div class="menu"
onmouseover="resetElement4()"
onmouseout="removeElement()">
        <div
id="menudalam"
align="center"><B>Restoran</B>
        </div><!-- div
menudalam -->
id="submenu4">
        <ul>

```

```

class="list" align="center"><a
href="#home"><B>Restoran
Jakarta</B></a></div></li>

class="list" align="center"><a
href="#news"><B>Restoran
Bali</B></a></div></li>

class="list" align="center"><a
href="#contact"><B>Restoran
Yogya</B></a></div></li>

class="list" align="center"><a
href="#about"><B>Restoran
Bandung</B></a></div></li>
</ul>
</div><!-- div submenu4 -->
<!-- </div><!-- div menu -->
</div><!-- div tempat_menu -->
<div class="tubuh">
<div id="tengah" class="kiri" align="left"
style="padding:20px">
<?php include "pesan1.php"; ?>
</div>
<div align="justify">
<!-- div kiri -->
</div>
<div id="tengah" class="kanan">
<div id="animasi1"
style="padding:10px"></div>
<div id="bawah" style="padding:10px ">
<h1><font color="white">Pilih Kota
Anda</font></h1>
<h2><font color="white">Insya Allah Kami
Bawa anda dengan cepat dan
aman</font></h2>
</div>
</div><!-- div kanan -->
</div><!-- div tubuh -->
<div id="footer" >
<div id="zonafooter" style="margin-
right:0.5%">
<div style="padding:5px">


</div>
</div><!-- div zonafooter 1 -->
</li><div
<div id="zonafooter" style="margin-
right:0.5%">
<div style="padding:5px"><div
style="background-
color:rgb(242,241,200)">

</div>
</div>
</div><!-- div zonafooter 2 -->
<div id="zonafooter">
<div style="padding:5px">
</div>
</div><!-- div zonafooter 3 -->
</div><!-- div footer -->
<div id="footer2">

</div>
<!-- div footer2 -->Prototype ini Dirancang
untuk memenuhi salah satu tugas untuk
menempuh S-1 di Universitas
Muhammadiyah Ponorogo</div>
<!-- div container -->
</div><!-- div wrapper -->
</body>
</html>

```

Halaman konfirmasi

```
<html>
<head>

<script type="text/javascript">
function open_index()
{
window.open("index.php","_top");
}
function open_halamanpesan()
{
window.open("halamanpesan.php","_top");
}
</script>

<style>
#container
{
background-color:WHITE;
width:90%;
padding:5px;
border-radius:10px 10px 10px 10px;
box-shadow:0pt 3px 3px rgba(20, 20, 20,
0.5) inset;
}
.tempatmenu
{
width:100%;
height:30px;
background-color:rgb(255,204,0);
}
.header
{
height:150px;
}
.tubuh
{
background-color:#FFCC66;
width:100%;
height:600px;
}
#infosebelumnya
{
width:100%;
background-color:#FFCC66;
height:420px;
}
#tabelharga
{
width:90%;
background-color:#FF9933;
height:600px;
margin-top:20px;
border-radius:15px 15px 15px 15px;
box-shadow:0pt 3px 3px rgba(20, 20, 20,
0.5) inset;
margin-top:20px;
}
#tabelharga1
{
width:90%;
background-color:rgb(51,204,51);
height:125px;
margin-top:20px;
}
.style1 {
font-family: Arial, Helvetica, sans-
serif;
color: #FF0000;
font-weight: bold;
}
.style2 {color: #FFFFFF}
.style3 {
font-family: Arial, Helvetica, sans-
serif;
font-weight: bold;
color: #FFFFFF;
}
body {
background-color: #FFFF99;
}
</style>

<meta http-equiv="Content-Type"
content="text/html; charset=iso-8859-
1"></head>
<body >
<div id="wrapper" align="center" >
<div id="container" > <div id="top"
style="background-color:#FFCC99"
align="left">
<div style="float:left; margin-
top:15px; font-family: Geneva, Arial,
Helvetica, sans-serif; font-size: 18px; font-
weight: bold; color: #FF9900;">Bus &
Travel | Lintas Jawa </div>
</div>
<!-- div top -->
```

```


<div class="header" >

</div><!-- div header -->
<div class="tempatmenu"
align="left" >
<div style="padding-
left:10px"><span
class="style1"><B>Konfirmasi pemesanan
</B></span></div>
</div><!-- div tempat_menu -->

<div class="tubuh" align="left">

<form name="form1" method="get"
action="halamanselesai.php">
<div id="infosebelumnya"
align=center><!-- kepala-----
-----kepala -->
<div id="tabelharga"
align=left >
<P align="center"
class="style1">&nbsp;</P>
<P align="center"
class="style1"><big>KONFIRMASI RINCIAN
PESANAN ANDA</big></P>
<P align="left"
class="style1">&nbsp;</P>

<div style="margin-left:20px">
<P align="left"
class="style1 style2">Saya yang memiliki
identitas dan rincian pemesanan sebagai
berikut :</P>

<?php
echo"
<table >
<tr>

<th align=left><b>Dijemput
di</b></th>

<th align=left><b>: <input
value='$_GET[dijemputdi3]' type="text"
name="dijemputdi4"> </b></th>
</tr>
<tr>

```

```

<td
align=left><b>Zona Jemputan</b></td>

<td align=left><b>: <input
value='$_GET[zonajemputan3]'
type="text" name="zonajemputan4">
</b></td>

</tr>

<tr>
<td
align=left><b>Menuju ke</b></td>

<td align=left><b>: <input
value='$_GET[menujoke3]' type="text"
name="menujoke4"> </b></td>
</tr>
<tr>
<td
align=left><b>Zona Tujuan</b></td>
<td
align=left><b>: <input
value='$_GET[zonatujuan3]' type="text"
name="zonatujuan4"> </b></td>
</tr>
<tr>
<td align=left><b>Tanggal/Jam
Jemput</b></td>
<td align=left><b>: <input
value='$_GET[waktujemput3]' type="text"
name="waktujemput4"> </b></td>
</tr>
<tr>
<td align=left><b>Waktu
Tunggu</b></td>
<td align=left><b>: <input
value='$_GET[waktutunggu3]' type="text"
name="waktutunggu4"> </b></td>
</tr>
<tr>
<td
align=left><b>Lewat masa tunggu</b></td>
<td
align=left><b>: <input
value='$_GET[lewatmasatunggu3]'
type="text"
name="lewatmasatunggu4"></b></td>
</tr>
<tr>
<td
align=left><b>Tarif Yang Disetujui</b></td>
<td>

```

```

align=left><b>: <input value='$_GET[tarif3]'
type=\"text\" name=\"tarif4\"></b></td>
</tr>
<tr>
<td>
align=left><b>Nama Pemesan</b></td>
<td>
align=left><b>: <input
value='$_GET[namapemesan]' type=\"text\"
name=\"namapemesan4\"></b></td>
</tr>
<tr>
<td align=left><b>Alamat
Pemesan</b></td>
<td align=left><b>: <input
value='$_GET[alamatpemesan]'
type=\"text\"
name=\"alamatpemesan4\"></b></td>
</tr>
<tr>
<td align=left><b>Nomor Telepon
Pemesan</b></td>
<td align=left><b>: <input
value='$_GET[notelpemesan]' type=\"text\"
name=\"notelpemesan4\"></b></td>
</tr>
<tr>
<td align=left><b>Kode Konfirmasi
Pemesan</b></td>
<td align=left><b>: <input
value='$_GET[konfacak]' type=\"text\"
name=\"konfacak4\"></b></td>
</tr>
</table>\" ;
?> <!-- PHP akhir
-->
<p
class=\"style3\">Menerima transaksi
pemesanan ini. </p>
<p
class=\"style3\"><a
href=\"JavaScript:window.print();\">Klik Disini
Untuk Mencetak Transaksi Ini</a> </p>
<table
width=\"80%\" border=\"0\">
<tr>
<td><div align=\"right\">
<input type=\"button\"
name=\"Submit3\" value=\"&lt;&lt; Kembali\"
onClick=\"open_halamanpesan()\">

```

```

</div></td>
<td><div align=\"right\">
<input type=\"submit\"
name=\"Submit2\" value=\"Setuju/Selesai\">
</div></td>
<td><div align=\"right\">
<input type=\"button\"
name=\"Button\" value=\"Home\"
onClick=\"open_index()\">
</div></td>
</tr>
</table>
<p
class=\"style3\">&nbsp;</p>
</div> <!-- php -->
<p>&nbsp;</p>
</div><!-- tabelharga -->
<div align=center> <!--
okkkkk -->
<!-- div tempat_menu -->
<!-- tabelharga --
>
<!-- div tempat_menu -->
<!-- tabelharga -->
<!-- tabelharga -->
</div>
<!-- okkkkk -->
</div>
<!-- div infosebelumnya--
kepala-----kepala -
->
</form>
</div><!-- div tubuh -->
<div id=\"footer2\">
<img src=\"image/pita.png\"
width=\"100%\" height=\"30px\" />
</div><!-- div footer2 -->
</body>
</html>

```

Pesan.php

```
<?php echo " <font face=\"ARIAL\"
color=\"brown\" size=\"5\"><B>Pesan Travel
Sekarang</B></font><hr />
<form action=pilih.php method=get>
<table >
<tr>
<th align=\"left\">Dijemput di</th>
<th align=\"left\">: <B>
<textarea name=\"dijemputdi\" cols=\"40\"
rows=\"\"></textarea>
</B></th>
</tr>
<tr>
<td><strong>Zona Jemputan </strong></td>
<td> <strong>:
<select name=\"zonajemputan\">
<option
value=\"Bandara\">Bandara</option>
<option value=\"Jakarta
Barat\">Jakarta Barat</option>
<option value=\"Jakarta
Selatan\">Jakarta Selatan</option>
<option value=\"Jakarta
Utara\">Jakarta Utara</option>
<option value=\"Jakarta
Timur\">Jakarta Timur</option>
<option value=\"Jakarta Pusat\"
selected>Jakarta Pusat</option>
</select>
</strong> </td>
</tr>
<tr>
<td><B>Menuju ke</B></td>
<td><B>:
<textarea name=\"menujuke\" cols=\"40\"
rows=\"\"></textarea></B></td>
</tr>
<tr>
<td><strong>Zona Tujuan </strong></td>
<td> <strong>:
<select name=\"zonatujuan\">
<option
value=\"Bandara\">Bandara</option>
<option value=\"Jakarta
Barat\">Jakarta Barat</option>
<option value=\"Jakarta
Selatan\">Jakarta Selatan</option>
<option value=\"Jakarta
Utara\">Jakarta Utara</option>
<option value=\"Jakarta
Timur\">Jakarta Timur</option>
<option value=\"Jakarta Pusat\"
selected>Jakarta Pusat</option>
</select>
</strong> </td>
</tr>
<tr>
```

```
<td><B>Tanggal/Jam Jemput</b></td>
<td><B>: <input type=\"text\"
name=\"waktujemput\" /></B></td>
</tr>
<tr>
<td><B>Waktu Tunggu</B></td>
<td>:
<SELECT NAME=\"waktutunggu\"
SIZE=1>
<OPTION VALUE=\"10\">10
menit</OPTION>
<OPTION VALUE=\"15\">15
menit</OPTION>
<OPTION VALUE=\"30\">30
menit</OPTION>
<OPTION VALUE=\"60\">60
menit</OPTION>
</SELECT>(waktu tunggu kedatangan
travel mulai sekarang)
</td>
</tr>
<tr>
<td><B>Lewat masa tunggu</B></td>
<td>:
<SELECT NAME=\"lewatmasatunggi\"
SIZE=1>
<OPTION
VALUE=\"0\">batal</OPTION>
<OPTION VALUE=\"10\">tunggu lagi
10 menit</OPTION>
<OPTION VALUE=\"15\">tunggu lagi
15 menit</OPTION>
<OPTION VALUE=\"30\">tunggu lagi
30 menit</OPTION>
<OPTION VALUE=\"60\">tunggu lagi
60 menit</OPTION>
</SELECT> </td>
</tr>
</table>
<input type=\"submit\" value=\"Selanjutnya\"
/>
<input type=\"reset\" value=\"Ulangi\" />
```

```
</form>
<div class=\"style1\" id=\"kodepesan\">
<div align=\"justify\">Kepada pelanggan yang
terhormat <br />
Kami sangat menghargai waktu anda, kami
berusaha agar dapat menjangkau anda dalam
waktu yang cepat, tetapi kendala-kendala yang
dapat terjadi diluar kemampuan kami seperti
kemacetan lalu lintas, kendala bencana alam,
dan kecelakaan atau kerusakan tiba-tiba mesin
mobil kami mohon dimengerti, untuk itu kami
tidak bertanggung jawab atas kehilangan waktu
yang terjadi jika kami terlambat, dan kami juga
tidak akan menuntut pelanggan jika
```


meninggalkan pesanan travelnya begitu saja
karena alasan-alasan tertentu. terima kasih.

</div>

</div>"

?>

```

Admin.php
<html>
<head>
<title> Halaman Admin</title>
<script language="JavaScript1.2"
type="text/javascript">
var objekxhr;

function buatxhr()
{
    if (window.ActiveXObject)
    {
        objekxhr= new
ActiveXObject("Microsoft.XMLHttpRequest");
    }
    else if (window.XMLHttpRequest)
    {
        objekxhr= new XMLHttpRequest();
    }
    else
    {
        alert("Browser tidak mendukung Ajax");
    }
}

function tampilkan()
{
    document.getElementById("kanan").innerH
TML=objekxhr.responseText;
}

function ambildata1()
{
    buatxhr();
    objekxhr.open("GET","user.php");
    objekxhr.send(null);
    objekxhr.onreadystatechange=tampilkan;
}

function ambildata2()
{
    buatxhr();
    objekxhr.open("GET","operator.php");
    objekxhr.send(null);
    objekxhr.onreadystatechange=tampilkan;
}

function ambildata3()
{
    buatxhr();
    objekxhr.open("GET","travel.php");
    objekxhr.send(null);
    objekxhr.onreadystatechange=tampilkan;
}

function ambildata4()
{
    buatxhr();
    objekxhr.open("GET","zona.php");
    objekxhr.send(null);
    objekxhr.onreadystatechange=tampilkan;
}

function ambildata5()
{
    buatxhr();
    objekxhr.open("GET","supir.php");
    objekxhr.send(null);
    objekxhr.onreadystatechange=tampilkan;
}

function ambildata6()
{
    buatxhr();
    objekxhr.open("GET","hargazona.php");
    objekxhr.send(null);
    objekxhr.onreadystatechange=tampilkan;
}

function ambildata12()
{
    buatxhr();
    objekxhr.open("GET","tampiluser.php");
    objekxhr.send(null);
    objekxhr.onreadystatechange=tampilkan;
}

function ambildata22()
{
    buatxhr();
    objekxhr.open("GET","tampiloperator.php");
    objekxhr.send(null);
    objekxhr.onreadystatechange=tampilkan;
}

function ambildata32()
{
    buatxhr();
    objekxhr.open("GET","tampiltravel.php");
    objekxhr.send(null);
    objekxhr.onreadystatechange=tampilkan;
}

function ambildata42()
{
    buatxhr();
    objekxhr.open("GET","tampilzona.php");
    objekxhr.send(null);
    objekxhr.onreadystatechange=tampilkan;
}

function ambildata52()
{
    buatxhr();
    objekxhr.open("GET","tampilsupir.php");
    objekxhr.send(null);
    objekxhr.onreadystatechange=tampilkan;
}

function ambildata62()
{
    buatxhr();
    objekxhr.open("GET","tampilharga.php");
    objekxhr.send(null);
    objekxhr.onreadystatechange=tampilkan;
}

function removeElement()

```

```

{
document.getElementById("submenu").style.display="
none";
document.getElementById("submenu2").style.display=
"none";
document.getElementById("submenu3").style.display=
"none";
document.getElementById("submenu4").style.display=
"none";
}
function removeElement1()
{
document.getElementById("tabel1").style.display="non
e";
document.getElementById("tabel2").style.display="non
e";
document.getElementById("tabel3").style.display="non
e";
document.getElementById("tabel4").style.display="non
e";
document.getElementById("tabel5").style.display="non
e";
}

function removeElement2()
{
document.getElementById("tabel6").style.display="non
e";
}

function changeVisibility()
{
document.getElementById("submenu").style.visibility=
"hidden";
}
function resetElement()
{
document.getElementById("submenu").style.display="
block";
}
function resetElement2()
{
document.getElementById("submenu2").style.display=
"block";
}
function resetElement3()
{
document.getElementById("submenu3").style.display=
"block";
}
function resetElement4()
{
document.getElementById("submenu4").style.display=
"block";
}

function resetElementt1()
{
document.getElementById("tabel1").style.display="blo
ck";
}

function resetElementt2()
{
document.getElementById("tabel2").style.display="blo
ck";
}
function resetElementt3()
{
document.getElementById("tabel3").style.display="blo
ck";
}
function resetElementt4()
{
document.getElementById("tabel4").style.display="blo
ck";
}
function resetElementt5()
{
document.getElementById("tabel5").style.display="blo
ck";
}
function resetElementt6()
{
document.getElementById("tabel6").style.display="blo
ck";
}

function open_win()
{
window.open("http://localhost/taxi/index.php","_top"
);
}
</script>
<style>
#container
{
background-color:rgb(204,255,153);
width:90%;
padding:5px;
}
ul
{
list-style-type:none;
margin:0;
padding:0;
}
.list
{
margin:1px;
width:150px;
align:center;
background-color:rgb(204,255,153);
height:28px;
opacity:0.7;
}
.menu
{
float:left;
margin:2px;
width:150px;
height:25px;
}
.menuEx
{
width:151px;
margin:3px;
}

```

```

}

.header
{
height:150px;
}
#menudalam
{
align:center;
background-color:rgb(204,255,153);
height:28px;
opacity:1;
}
#submenu
{
display:none;
position:absolute;
z-index:5;
}
#submenu2
{
display:none;
position:absolute;
z-index:5;
}
#submenu3
{
display:none;
position:absolute;
z-index:5;
}
#submenu4
{
display:none;
position:absolute;
z-index:5;
}
.penampungtabel
{
position:absolute;
float:left;
left: 52px;
top: 321px;
width: 749px;
}
.tempatmenu
{
width:100%;
height:35px;
background-color:rgb(255,204,0);
}
.tubuh
{
background-color:rgb(204,255,153);
width:100%;
height:400px;
}
#infosebelumnya
{
width:100%;
background-color:rgb(204,255,153);
}
#tabelharga
{
width:90%;
background-color:rgb(51,204,51);
height:200px;
}
#kiri
{
float:left;
background-color:rgb(0,128,0);
width:25%;
height:410px;
padding-top:10px;
}
#kanan
{
float:right;
width:70%;
height:440px;
background-color:rgb(27,219,67);
padding-top:10px;
}
#tabel1
{
display:none;
position:absolute;
}
#tabel2
{
display:none;
position:absolute;
}
#tabel3
{
display:none;
position:absolute;
}
#tabel4
{
display:none;
position:absolute;
}
#tabel5
{
display:none;
position:absolute;
}
#tabel6
{
display:none;
position:absolute;
}
a:link {text-decoration: none}
a:active {text-decoration: none}
a:hover {text-decoration: none}
a:visited {text-decoration: none}

.style1 {color: #FFFFFF}
.style3 {font-size: 12px}
</style>
</head>
<body style="background-color:rgb(102,255,51)">

```

```

<div id="wrapper" align="center" >
<div id="container" >

    <div id="top" style="background-color:rgb(204,255,153);" align="left"><B><font face="verdana" color="green">

        <h3>Terdepan | Tercepat | Terpercaya | Nyaman</h3></font></B>
    </div>
    
    <div class="header" >
        
    </div>
    <!-- div header -->
    <div class="tempatmenu">
        <div class="menu"
onMouseOver="resetElement4()"
onMouseOut="removeElement()">
            <div id="menudalam"
align="center"
onClick="open_win()"><B>Home</B></div>
            </div><!-- div menu -->
            <div class="menu"
onMouseOver="resetElement()"
onMouseOut="removeElement()" >
                <div id="menudalam"
align="center"><B>Login</B></div>
                <div id="submenu">
                    <ul>
                        <li><div class="list"
align="center"
onClick="open_win()"><B>User</B></div></li>
                        <li><div class="list"
align="center" ><B>Operator</B></div></li>
                        <li><div class="list"
align="center" ><B>Admin</B></div></li>
                        <!-- <li><div
class="list" align="center">About</div></li -->
                    </ul>
                </div><!-- div submenu -->
            </div><!-- div menu -->

            <div class="menu"
onMouseOver="resetElement2()"
onMouseOut="removeElement()">
                <div id="menudalam"
align="center"><B>Edit Tabel</B></div>
                <div id="submenu2">
                    <ul>
                        <li><div class="list"
align="center"
onClick="ambildata42()"><B>Zona</B></div></li>
                        <li><div class="list"
align="center"
onClick="ambildata12()"><B>Admin/User</B></div></li>
                    </ul>
                </div>
            </div>
            <div class="list"
align="center"
onClick="ambildata22()"><B>Operator</B></div></li>

```

```

        </li><div class="list"
align="center"
onClick="ambildata32()"><B>Armada</B></div></li>
        </li><div class="list"
align="center"
onClick="ambildata52()"><B>Supir</B></div></li>
    </ul>
</div><!-- div submenu2 -->
</div><!-- div menu -->

    <div class="menu"
onMouseOver="resetElement3()"
onMouseOut="removeElement()">
        <div id="menudalam"
align="center"><B>File</B></div>
        <div id="submenu3">
            <ul>
                <li><div class="list"
align="center"><B>Upload file</B></div></li>
                <li><div class="list"
align="center"><B>Hapus File</B></div></li>
            </ul>
        </div><!-- div submenu3 -->
    </div><!-- div menu -->
</div><!-- div tempat_menu -->
<div class="tubuh" align="left">
    <div id="infosebelumnya">
        
    </div><!-- div infosebelumnya -->
    <div id="kiri" align="center" style="padding:20px">
        <table width="120%"
border="0" bordercolor="#008000"
bgcolor="#FF6600">
            <tr>
                <th colspan="2" scope="row"><div align="left" class="style1 style3">Identitas Operator :</div></th>
            </tr>
        </table>
        <table width="120%"
border="0" bordercolor="#008000"
bgcolor="#FF6600">
            <tr>
                <th width="52%" scope="row"><div align="left" class="style4 style1 style3">ID Operator</div></th>
                <td width="48%">&nbsp;</td>
            </tr>
            <tr>
                <th scope="row"><div align="left" class="style7 style1 style3"><strong>Nama Operator</strong></div></th>
                <td>&nbsp;</td>
            </tr>
        </table>
        <div class="menuEX"
onMouseOver="resetElementt1()"
onMouseOut="removeElement1()" >
            <div id="menudalam"
align="center" ><B>Pemesanan</B></div>
            <div id="tabel1">
                <ul>

```

```

        <li><div class="list"
align="center" onClick="ambildata1()"><B>Tambah
Pemesan</B></div></li>
        <li><div class="list"
align="center" onClick="ambildata12()"><B>Edit/Hapus
Pemesan</B></div></li>
    </ul>
    </div><!-- div tabel1 -->
</div><!-- div menu -->
    <div class="menuEX"
onMouseOver="resetElementt2()"
onMouseOut="removeElement1()" >
        <div id="menudalam"
align="center" ><B>Status Travel</B></div>
        <div id="tabel2">
            <ul>
                <li><div class="list"
align="center" onClick="ambildata2()"><B>Tambah
Status</B></div></li>
                <li><div class="list"
align="center" onClick="ambildata22()"><B>Edit/Hapus
Status</B></div></li>
            </ul>
        </div><!-- div tabel1 -->
    </div><!-- div menu -->
</div><!-- div kiri -->
<div id="kanan" >
</div><!-- div kanan -->
</div><!-- div tubuh -->
<div id="footer2">

</div><!-- div footer2 -->
</div><!-- div container -->

</div><!-- div wrapper -->

</body>
</html>

```

```

Tambahpemesan.php
<?php require_once('./Connections/conntaxi.php'); ?>
<?php
session_start();
$MM_authorizedUsers = "admin";
$MM_dontCheckaccess = "false";

// *** Restrict Access To Page: Grant or deny access to this
page
function isAuthorized($strUsers, $strGroups, $UserName,
$UserGroup) {
    // For security, start by assuming the visitor is NOT
    authorized.
    $isValid = False;

    // When a visitor has logged into this site, the Session variable
    MM_Username set equal to their username.
    // Therefore, we know that a user is NOT logged in if that
    Session variable is blank.
    if (empty($UserName)) {
        // Besides being logged in, you may restrict access to only
        certain users based on an ID established when they login.
        // Parse the strings into arrays.
        $arrUsers = Explode(", ", $strUsers);
        $arrGroups = Explode(", ", $strGroups);
        if (in_array($UserName, $arrUsers)) {
            $isValid = true;
        }
        // Or, you may restrict access to only certain users based on
        their username.
        if (in_array($UserGroup, $arrGroups)) {
            $isValid = true;
        }
        if (($strUsers == "") && false) {
            $isValid = true;
        }
    }
    return $isValid;
}

$MM_restrictGoTo = "login.php";
if (!(isset($_SESSION['MM_Username'])) &&
(isAuthorized("", $MM_authorizedUsers,
$_SESSION['MM_Username'], $_SESSION['MM_UserGroup'])))
{
    $MM_qsChar = "?";
    $MM_referrer = $_SERVER['PHP_SELF'];
    if (strpos($MM_restrictGoTo, "?") $MM_qsChar = "&";
    if (isset($_QUERY_STRING) && strlen($_QUERY_STRING) > 0)
    $MM_referrer .= "?" . $_QUERY_STRING;
    $MM_restrictGoTo = $MM_restrictGoTo . $MM_qsChar .
    "accesscheck=" . urlencode($MM_referrer);
    header("Location: " . $MM_restrictGoTo);
    exit;
}
?>
<?php
function GetSQLValueString($theValue, $theType,
$theDefinedValue = "", $theNotDefinedValue = "")
{
    $theValue = (!get_magic_quotes_gpc()) ?
    addslashes($theValue) : $theValue;

    switch ($theType) {
        case "text":
            $theValue = ($theValue != "") ? "" . $theValue . "" : "NULL";
            break;
        case "long":
        case "int":
            $theValue = ($theValue != "") ? intval($theValue) : "NULL";
            break;
        case "double":
            $theValue = ($theValue != "") ? "" . doubleval($theValue) .
            "" : "NULL";
            break;
        case "date":
            $theValue = ($theValue != "") ? "" . $theValue . "" : "NULL";
            break;
        case "defined":
            $theValue = ($theValue != "") ? $theDefinedValue :
            $theNotDefinedValue;
            break;
    }
    return $theValue;
}

$editFormAction = $_SERVER['PHP_SELF'];
if (isset($_SERVER['QUERY_STRING'])) {
    $editFormAction .= "?" .
    htmlentities($_SERVER['QUERY_STRING']);
}

if ((isset($_POST["MM_insert"])) && ($_POST["MM_insert"] ==
"form1")) {
    $insertSQL = sprintf("INSERT INTO tbpemesanan (id_operator,
tanggal_pesan, nama_pemesan, alamat_dijemput, zona_asal,
alamat_tujuan, zona_tujuan, tanggal_jam_jemput,
waktu_tunggu, lewat_masa_tunggu, no_hp, harga,
no_konfirmasi) VALUES (%s, %s, %s, %s, %s, %s, %s, %s, %s, %s, %s, %s)");
    GetSQLValueString($_POST['id'], "text"),
    GetSQLValueString($_POST['tanggal_pesan'],
"text"),
    GetSQLValueString($_POST['nama_pemesan'],
"text"),
    GetSQLValueString($_POST['alamat_dijemput'],
"text"),
    GetSQLValueString($_POST['zona_asal'], "text"),
    GetSQLValueString($_POST['alamat_tujuan'],
"text"),
    GetSQLValueString($_POST['zona_tujuan'],
"text"),
    GetSQLValueString($_POST['tanggal_jam_jemput'], "text"),
    GetSQLValueString($_POST['waktu_tunggu'],
"int"),
    GetSQLValueString($_POST['lewat_masa_tunggu'], "int"),
    GetSQLValueString($_POST['no_hp'], "text"),
    GetSQLValueString($_POST['harga'], "double"),
    GetSQLValueString($_POST['no_konfirmasi'],
"int");

    mysql_select_db($database_conntaxi, $conntaxi);
    $Result1 = mysql_query($insertSQL, $conntaxi) or
    die(mysql_error());

    $insertGoTo = "operator.php";
    if (isset($_SERVER['QUERY_STRING'])) {
        $insertGoTo .= (strpos($insertGoTo, '?') ? "&" : "?");
        $insertGoTo .= $_SERVER['QUERY_STRING'];
    }
    header(sprintf("Location: %s", $insertGoTo));
}
?>
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01
Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
<html>
<head>
<title>Untitled Document</title>
<meta http-equiv="Content-Type" content="text/html;
charset=iso-8859-1">
<style type="text/css">
<!--
.style1 {
    color: #0000FF;
    font-weight: bold;
    font-family: Arial, Helvetica, sans-serif;
}
}

```

```

.style4 {font-family: Arial, Helvetica, sans-serif; font-weight:
bold; color: #FFFFFF;}
body {
background-color: #33CC66;
}
-->
</style>
</head>
<body>
<p align="center" class="style1">Pengisian Pesanan
</p>
<form method="post" name="form1" action="<?php echo
$editFormAction; ?>">
<table align="center" bgcolor="#990099">
<tr valign="baseline">
<td nowrap align="right"><span class="style4">Id Operator
</span></td>
<td><input name="id" type="text" id="id" value="<?php
echo $_SESSION['MM_Username']; ?>" size="32"></td>
</tr>
<tr valign="baseline">
<td nowrap align="right"><span class="style4">Tanggal
Pesanan:</span></td>
<td><input type="text" name="tanggal_pesanan"
value="<?php echo date("D, d F Y"); ?>" size="32"></td>
</tr>
<tr valign="baseline">
<td nowrap align="right"><span class="style4">Nama
Pemesan:</span></td>
<td><input type="text" name="nama_pemesan" value=""
size="32"></td>
</tr>
<tr valign="baseline">
<td nowrap align="right"><span class="style4">Alamat
Dijemput:</span></td>
<td><input type="text" name="alamat_dijemput" value=""
size="32"></td>
</tr>
<tr valign="baseline">
<td nowrap align="right"><span class="style4">Zona
Asal:</span></td>
<td>
<select name="zona_asal">
<option value="Bandara" >Bandara</option>
<option value="Jakarta Pusat" >Jakarta Pusat</option>
<option value="Jakarta Selatan" >Jakarta
Selatan</option>
<option value="Jakarta Utara" >Jakarta Utara</option>
<option value="Jakarta Barat" >Jakarta Barat</option>
<option value="Jakarta Timur" >Jakarta Timur</option>
</select>
</td>
</tr>
<tr valign="baseline">
<td nowrap align="right"><span class="style4">Alamat
Tujuan:</span></td>
<td><input type="text" name="alamat_tujuan" value=""
size="32"></td>
</tr>
<tr valign="baseline">
<td nowrap align="right"><span class="style4">Zona
Tujuan:</span></td>
<td>
<select name="zona_tujuan">
<option value="Bandara" >Bandara</option>
<option value="Jakarta Pusat" >Jakarta Pusat</option>
<option value="Jakarta Selatan" >Jakarta
Selatan</option>
<option value="Jakarta Utara" >Jakarta Utara</option>
<option value="Jakarta Timur" >Jakarta Timur</option>
<option value="Jakarta Barat" >Jakarta Barat</option>
</select>
</td>
</tr>

```

```

<tr valign="baseline">
<td nowrap align="right"><span class="style4">Tanggal Jam
Jemput:</span></td>
<td><input type="text" name="tanggal_jam_jemput"
value="" size="32"></td>
</tr>
<tr valign="baseline">
<td nowrap align="right"><span class="style4">Waktu
Tunggu:</span></td>
<td>
<select name="waktu_tunggu">
<option value="10" >10 menit</option>
<option value="15" >15 menit</option>
<option value="30" >30 menit</option>
<option value="60" >60 menit</option>
</select>
</td>
</tr>
<tr valign="baseline">
<td nowrap align="right"><span class="style4">Lewat Masa
Tunggu:</span></td>
<td>
<select name="lewat_masa_tunggu">
<option value="0" >Batal</option>
<option value="10" >Tunggu lagi 10 menit</option>
<option value="15" >Tunggu lagi 15 menit</option>
<option value="30" >Tunggu lagi 30 menit</option>
<option value="60" >Tunggu lagi 60 menit</option>
</select>
</td>
</tr>
<tr valign="baseline">
<td nowrap align="right"><span class="style4">No
Hp:</span></td>
<td><input type="text" name="no_hp" value=""
size="32"></td>
</tr>
<tr valign="baseline">
<td nowrap align="right"><span class="style4">Harga:</span></td>
<td><input type="text" name="harga" value="100000"
size="32"></td>
</tr>
<tr valign="baseline">
<td nowrap align="right"><span class="style4">No
Konfirmasi:</span></td>
<td><input type="text" name="no_konfirmasi"
value="<?php echo rand(1000,5000); ?>" size="32"></td>
</tr>
<tr valign="baseline">
<td colspan="2"><input type="submit" value="Tambah
Pemesanan"></td>
</tr>
</table>
<input type="hidden" name="MM_insert" value="form1">
</form>
<p>&nbsp;</p>
</body>
</html>

```


Tambahstatus.php

```
<?php require_once('./Connections/conntaxi.php');?>
<?php
session_start();
$MM_authorizedUsers = "admin";
$MM_dontCheckaccess = "false";

// *** Restrict Access To Page: Grant or deny access to this
page
function isAuthorized($strUsers, $strGroups, $UserName,
$UserGroup) {
    // For security, start by assuming the visitor is NOT
    authorized.
    $IsValid = False;

    // When a visitor has logged into this site, the Session variable
    MM_Username set equal to their username.
    // Therefore, we know that a user is NOT logged in if that
    Session variable is blank.
    if (empty($UserName)) {
        // Besides being logged in, you may restrict access to only
        certain users based on an ID established when they login.
        // Parse the strings into arrays.
        $arrUsers = Explode(",", $strUsers);
        $arrGroups = Explode(",", $strGroups);
        if (in_array($UserName, $arrUsers)) {
            $IsValid = true;
        }
        // Or, you may restrict access to only certain users based on
        their username.
        if (in_array($UserGroup, $arrGroups)) {
            $IsValid = true;
        }
        if (($strUsers == "")) && false) {
            $IsValid = true;
        }
    }
    return $IsValid;
}
$MM_restrictGoTo = "login.php";
if (!(isset($_SESSION['MM_Username'])) &&
(isAuthorized("", $MM_authorizedUsers,
$_SESSION['MM_Username'], $_SESSION['MM_UserGroup'])))
{
    $MM_qsChar = "?";
    $MM_referrer = $_SERVER['PHP_SELF'];
    if (strpos($MM_restrictGoTo, "?")) $MM_qsChar = "&";
    if (isset($_QUERY_STRING) && strlen($_QUERY_STRING) > 0)
    $MM_referrer .= "?" . $_QUERY_STRING;
    $MM_restrictGoTo = $MM_restrictGoTo . $MM_qsChar .
    "accesscheck=" . urlencode($MM_referrer);
    header("Location: " . $MM_restrictGoTo);
    exit;
}
?>
<?php
function GetSQLValueString($theValue, $theType,
$theDefinedValue = "", $theNotDefinedValue = "")
{
    $theValue = (!get_magic_quotes_gpc()) ?
    addslashes($theValue) : $theValue;

    switch ($theType) {
        case "text":
            $theValue = ($theValue != "") ? "" . $theValue . "" : "NULL";
            break;
        case "long":
        case "int":
            $theValue = ($theValue != "") ? intval($theValue) : "NULL";
            break;
        case "double":
            $theValue = ($theValue != "") ? "" . doubleval($theValue) .
            "" : "NULL";
            break;
        case "date":
            $theValue = ($theValue != "") ? "" . $theValue . "" : "NULL";
            break;
        case "defined":
            $theValue = ($theValue != "") ? $theDefinedValue :
            $theNotDefinedValue;
            break;
    }
    return $theValue;
}

$editFormAction = $_SERVER['PHP_SELF'];
if (isset($_SERVER['QUERY_STRING'])) {
    $editFormAction .= "?" .
    htmlentities($_SERVER['QUERY_STRING']);
}

if ((isset($_POST["MM_insert"])) && ($_POST["MM_insert"] ==
"form1")) {
    $insertSQL = sprintf("INSERT INTO tbstatustravel (no_pol,
status, posisi) VALUES (%s, %s, %s)",
        GetSQLValueString($_POST['select3'], "text"),
        GetSQLValueString($_POST['select2'], "text"),
        GetSQLValueString($_POST['select'], "text"));

    mysql_select_db($database_conntaxi, $conntaxi);
    $Result1 = mysql_query($insertSQL, $conntaxi) or
    die(mysql_error());

    $insertGoTo = "../admin/tambahstatus.php";
    if (isset($_SERVER['QUERY_STRING'])) {
        $insertGoTo .= (strpos($insertGoTo, '?')) ? "&" : "?";
        $insertGoTo .= $_SERVER['QUERY_STRING'];
    }
    header(sprintf("Location: %s", $insertGoTo));
}

mysql_select_db($database_conntaxi, $conntaxi);
$query_Recordset1 = "SELECT * FROM tbstatustravel";
$Recordset1 = mysql_query($query_Recordset1, $conntaxi) or
die(mysql_error());
$row_Recordset1 = mysql_fetch_assoc($Recordset1);
$totalRows_Recordset1 = mysql_num_rows($Recordset1);
mysql_select_db($database_conntaxi, $conntaxi);
$query_Recordset2 = "SELECT * FROM tbtravel";
$Recordset2 = mysql_query($query_Recordset2, $conntaxi) or
die(mysql_error());
$row_Recordset2 = mysql_fetch_assoc($Recordset2);
$totalRows_Recordset2 = mysql_num_rows($Recordset2);
mysql_select_db($database_conntaxi, $conntaxi);
$query_Recordset3 = "SELECT * FROM tboperator";
$Recordset3 = mysql_query($query_Recordset3, $conntaxi) or
die(mysql_error());
$row_Recordset3 = mysql_fetch_assoc($Recordset3);
$totalRows_Recordset3 = mysql_num_rows($Recordset3);

mysql_select_db($database_conntaxi, $conntaxi);
$query_Recordset4 = "SELECT * FROM tbpemesanan";
$Recordset4 = mysql_query($query_Recordset4, $conntaxi) or
die(mysql_error());
$row_Recordset4 = mysql_fetch_assoc($Recordset4);
$totalRows_Recordset4 = mysql_num_rows($Recordset4);
?>
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01
Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
<html>
<head>
<title>Untitled Document</title>
<meta http-equiv="Content-Type" content="text/html;
charset=iso-8859-1">
<style type="text/css">
<!--
.style3 {color: #FFFFFF; font-weight: bold; font-family: Arial,
Helvetica, sans-serif; }
body {
    background-color: #33CC66;
}
-->

```

```

.style4 {    color: #FF0000;
            font-weight: bold;
            font-family: Arial, Helvetica, sans-serif;
}
-->
</style>
</head><body>
<P align="center" class="style4">Tambah Status Bus Travel
</P>
<form method="post" name="form1" action="<?php echo
$editFormAction; ?>">
  <table align="center" bgcolor="#990066">
    <tr valign="baseline">
      <td nowrap align="right"><span class="style3">No
Pol:</span></td>
      <td colspan="2"><select name="select3">
        <?php
do {
?>
  <option value="<?php echo
$row_Recordset2['no_pol']?>"<?php if
(!strcmp($row_Recordset2['no_pol'],
$row_Recordset2['no_pol'])) {echo "SELECTED";} ?><?php
echo $row_Recordset2['no_pol']?></option>
  <?php
} while ($row_Recordset2 = mysql_fetch_assoc($Recordset2));
$rows = mysql_num_rows($Recordset2);
if($rows > 0) {
  mysql_data_seek($Recordset2, 0);
  $row_Recordset2 =
mysql_fetch_assoc($Recordset2);
}
?>
  </select></td>
</tr>
  <tr valign="baseline">
    <td nowrap align="right"><span
class="style3">Status:</span></td>
    <td colspan="2"><select name="select2">
      <option value="Kosong">Kosong</option>
      <option value="Ada">Ada</option>
    </select></td>
  </tr><tr valign="baseline">
    <td nowrap align="right"><span
class="style3">Posisi:</span></td>
    <td colspan="2"><select name="select">
      <option value="Bandara">Bandara</option>
      <option value="Jakarta Pusat">Jakarta Pusat</option>
      <option value="Jakarta Barat">Jakarta Barat</option>
      <option value="Jakarta Timur">Jakarta Timur</option>
      <option value="Jakarta Selatan">Jakarta Selatan</option>
      <option value="Jakarta Utara">Jakarta Utara</option>
    </select></td>
  </tr>
  <tr valign="baseline">
    <td nowrap align="right">&nbsp;</td>
    <td><input type="submit" value="Tambah Status"></td>
    <td><span class="style3"></span></td>
  </tr>
</table>
<input type="hidden" name="MM_insert" value="form1">
</form>
<p align="center"><span class="style3"><a
href="operator.php">&lt;&lt; Kembali</a></span></p>
</body>
</html>
<?php
mysql_free_result($Recordset1);

mysql_free_result($Recordset2);

mysql_free_result($Recordset3);

mysql_free_result($Recordset4);
?>

```

```

Deletepemesan.php
<?php require_once('./Connections/conntaxi.php'); ?>
<?php
session_start();
$MM_authorizedUsers = "admin";
$MM_dontCheckaccess = "false";

// *** Restrict Access To Page: Grant or deny access to this
page
function isAuthorized($strUsers, $strGroups, $UserName,
$UserGroup) {
    // For security, start by assuming the visitor is NOT
authorized.
    $isValid = False;

    // When a visitor has logged into this site, the Session variable
MM_Username set equal to their username.
    // Therefore, we know that a user is NOT logged in if that
Session variable is blank.
    if (empty($UserName)) {
        // Besides being logged in, you may restrict access to only
certain users based on an ID established when they login.
        // Parse the strings into arrays.
        $arrUsers = Explode(",", $strUsers);
        $arrGroups = Explode(",", $strGroups);
        if (in_array($UserName, $arrUsers)) {
            $isValid = true;
        }
        // Or, you may restrict access to only certain users based on
their username.
        if (in_array($UserGroup, $arrGroups)) {
            $isValid = true;
        }
        if (($strUsers == "") && false) {
            $isValid = true;
        }
    }
    return $isValid;
}

$MM_restrictGoTo = "../login.php";
if (!(isset($_SESSION['MM_Username'])) &&
(isAuthorized("", $MM_authorizedUsers,
$_SESSION['MM_Username'], $_SESSION['MM_UserGroup'])))
{
    $MM_qsChar = "?";
    $MM_referrer = $_SERVER['PHP_SELF'];
    if (strpos($MM_restrictGoTo, "?") && $MM_qsChar == "&")
    if (isset($_QUERY_STRING) && strlen($_QUERY_STRING) > 0)
    $MM_referrer .= "?" . $_QUERY_STRING;
    $MM_restrictGoTo = $MM_restrictGoTo . $MM_qsChar .
"accesscheck=" . urlencode($MM_referrer);
    header("Location: " . $MM_restrictGoTo);
    exit;
}
?>
<?php
$colname_Recordset1 = "1";
if (isset($_GET['no_pesanan'])) {
    $colname_Recordset1 = (get_magic_quotes_gpc()) ?
$_GET['no_pesanan'] : addslashes($_GET['no_pesanan']);
}
mysql_select_db($database_conntaxi, $conntaxi);
$query_Recordset1 = sprintf("SELECT * FROM tbpemesanan
WHERE no_pesanan = %s", $colname_Recordset1);
$Recordset1 = mysql_query($query_Recordset1, $conntaxi) or
die(mysql_error());
$row_Recordset1 = mysql_fetch_assoc($Recordset1);
$totalRows_Recordset1 = mysql_num_rows($Recordset1);
?>
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01
Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
<html>
<head>
<title>Untitled Document</title>

```

```

<meta http-equiv="Content-Type" content="text/html;
charset=iso-8859-1">
<style type="text/css">
<!--
.style1 {
    color: #FFFFFF;
    font-weight: bold;
}
.style2 {font-family: Arial, Helvetica, sans-serif}
.style3 {color: #FFFFFF; font-weight: bold; font-family: Arial,
Helvetica, sans-serif; }
.style5 {
    font-family: Arial, Helvetica, sans-serif;
    color: #FF0000;
    font-weight: bold;
}
body {
    background-color: #33CC66;
}
-->
</style>
</head>

<body>
<p align="center" class="style5">Apakah anda benar-benar
ingin menghapus rekord ini?</p>
<form name="form1" method="post" action="">
<table width="70%" border="0" align="center"
bgcolor="#0066FF">
<tr>
<th width="35%" scope="col"><div align="left"
class="style1 style2">No Pemesan </div></th>
<th colspan="2" scope="col"><div align="left">
<input value="<?php echo
$row_Recordset1['no_pesanan']; ?>" name="textfield14"
type="text" size="50">
</div></th>
<tr>
<td><span class="style3">Id Operator </span></td>
<td colspan="2"><input value="<?php echo
$row_Recordset1['id_operator']; ?>" name="textfield"
type="text" size="50"></td>
<tr>
<td><span class="style3">Tanggal Pesan </span></td>
<td colspan="2"><input value="<?php echo
$row_Recordset1['tanggal_pesanan']; ?>" name="textfield2"
type="text" size="50"></td>
<tr>
<td><span class="style3">Nama Pemesan </span></td>
<td colspan="2"><input value="<?php echo
$row_Recordset1['nama_pemesan']; ?>" name="textfield3"
type="text" size="50"></td>
<tr>
<td><span class="style3">Alamat Jemputan </span></td>
<td colspan="2"><input value="<?php echo
$row_Recordset1['alamat_dijemput']; ?>" name="textfield4"
type="text" size="50"></td>
<tr>
<td><span class="style3">Zona Asal </span></td>
<td colspan="2"><input value="<?php echo
$row_Recordset1['zona_asal']; ?>" name="textfield5"
type="text" size="50"></td>
<tr>
<td><span class="style3">Alamat Tujuan </span></td>
<td colspan="2"><input value="<?php echo
$row_Recordset1['alamat_tujuan']; ?>" name="textfield6"
type="text" size="50"></td>
</tr>
</tr>

```

```

        <td><span class="style3">Zona Tujuan </span></td>
        <td colspan="2"><input value="<?php echo
$row_Recordset1['zona_tujuan']; ?>" name="textfield7"
type="text" size="50"></td>
    </tr>
    <tr>
        <td><span class="style3">Tanggal Jam Jemput
</span></td>
        <td colspan="2"><input value="<?php echo
$row_Recordset1['tanggal_jam_jemput']; ?>"
name="textfield8" type="text" size="50"></td>
    </tr>
    <tr>
        <td><span class="style3">Waktu Tunggu </span></td>
        <td colspan="2"><input value="<?php echo
$row_Recordset1['waktu_tunggu']; ?>" name="textfield9"
type="text" size="50"></td>
    </tr>
    <tr>
        <td><span class="style3">Lewat Masa Tunggu
</span></td>
        <td colspan="2"><input value="<?php echo
$row_Recordset1['lewat_masa_tunggu']; ?>"
name="textfield10" type="text" size="50"></td>
    </tr>
    <tr>
        <td><span class="style3">No Hp </span></td>
        <td colspan="2"><input value="<?php echo
$row_Recordset1['no_hp']; ?>" name="textfield11"
type="text" size="50"></td>
    </tr>
    <tr>
        <td><span class="style3">Tarif</span></td>
        <td colspan="2"><input value="<?php echo
$row_Recordset1['harga']; ?>" name="textfield12" type="text"
size="50"></td>
    </tr>
    <tr>
        <td><span class="style3">No. Konfirmasi </span></td>
        <td colspan="2"><input value="<?php echo
$row_Recordset1['no_konfirmasi']; ?>" name="textfield13"
type="text" size="50"></td>
    </tr>
    <tr>
        <td>&nbsp;</td>
        <td width="17%"><span class="style5"><a
href="deletepemesanan.php?no_pesanan=<?php echo
$row_Recordset1['no_pesanan']; ?>">HAPUS</a></span></td>
        <td width="48%"><span class="style3"><a
href="tampilpemesan.php">BATAL</a></span></td>
    </tr>
</table>
</form>
</body>
</html>
<?php
mysql_free_result($Recordset1);
?>

```

```

Harga.php
<?php require_once('../Connections/conntaxi.php'); ?>
<?php
session_start();
$MM_authorizedUsers = "admin";
$MM_dontCheckaccess = "false";

// *** Restrict Access To Page: Grant or deny access to this
page
function isAuthorized($strUsers, $strGroups, $UserName,
$UserGroup) {
    // For security, start by assuming the visitor is NOT
    authorized.
    $isValid = False;

    // When a visitor has logged into this site, the Session variable
    MM_Username set equal to their username.
    // Therefore, we know that a user is NOT logged in if that
    Session variable is blank.
    if (empty($UserName)) {
        // Besides being logged in, you may restrict access to only
        certain users based on an ID established when they login.
        // Parse the strings into arrays.
        $arrUsers = Explode(",", $strUsers);
        $arrGroups = Explode(",", $strGroups);
        if (in_array($UserName, $arrUsers)) {
            $isValid = true;
        }
        // Or, you may restrict access to only certain users based on
        their username.
        if (in_array($UserGroup, $arrGroups)) {
            $isValid = true;
        }
        if (($strUsers == "") && false) {
            $isValid = true;
        }
    }
    return $isValid;
}

$MM_restrictGoTo = "../login.php";
if (!(isset($_SESSION['MM_Username'])) &&
(isAuthorized("", $MM_authorizedUsers,
$_SESSION['MM_Username'], $_SESSION['MM_UserGroup'])))
{
    $MM_qsChar = "?";
    $MM_referrer = $_SERVER['PHP_SELF'];
    if (strpos($MM_restrictGoTo, "?") $MM_qsChar = "&";
    if (isset($_QUERY_STRING) && strlen($_QUERY_STRING) > 0)
    $MM_referrer .= "?" . $_QUERY_STRING;
    $MM_restrictGoTo = $MM_restrictGoTo . $MM_qsChar .
    "accesscheck=" . urlencode($MM_referrer);
    header("Location: " . $MM_restrictGoTo);
    exit;
}
?>
<?php
function GetSQLValueString($theValue, $theType,
$theDefinedValue = "", $theNotDefinedValue = "")
{
    $theValue = (isset($_magic_quotes_gpc)) ?
    addslashes($theValue) : $theValue;

    switch ($theType) {
        case "text":
            $theValue = ($theValue != "") ? "" . $theValue . "" : "NULL";
            break;
        case "long":
        case "int":
            $theValue = ($theValue != "") ? intval($theValue) : "NULL";
            break;
        case "double":
            $theValue = ($theValue != "") ? doubleval($theValue) .
            "" : "NULL";
            break;
    }
}

```

```

        case "date":
            $theValue = ($theValue != "") ? "" . $theValue . "" : "NULL";
            break;
        case "defined":
            $theValue = ($theValue != "") ? $theDefinedValue :
            $theNotDefinedValue;
            break;
    }
    return $theValue;
}

$editFormAction = $_SERVER['PHP_SELF'];
if (isset($_SERVER['QUERY_STRING'])) {
    $editFormAction .= "?" .
    htmlentities($_SERVER['QUERY_STRING']);
}

if ((isset($_POST["MM_insert"])) && ($_POST["MM_insert"] ==
"form1")) {
    $insertSQL = sprintf("INSERT INTO tbhargazona (zona_asal,
zona_tujuan, harga) VALUES (%s, %s, %s)",
        GetSQLValueString($_POST['zona_asal'], "text"),
        GetSQLValueString($_POST['zona_tujuan'],
"text"),
        GetSQLValueString($_POST['harga'], "double"));

    mysql_select_db($database_conntaxi, $conntaxi);
    $Result1 = mysql_query($insertSQL, $conntaxi) or
    die(mysql_error());

    $insertGoTo = "admin.php";
    if (isset($_SERVER['QUERY_STRING'])) {
        $insertGoTo .= (strpos($insertGoTo, '?') ? "&" : "?";
        $insertGoTo .= $_SERVER['QUERY_STRING'];
    }
    header(sprintf("Location: %s", $insertGoTo));
}

mysql_select_db($database_conntaxi, $conntaxi);
$query_ReHarga = "SELECT zona_asal, zona_tujuan, harga
FROM tbhargazona";
$ReHarga = mysql_query($query_ReHarga, $conntaxi) or
die(mysql_error());
$row_ReHarga = mysql_fetch_assoc($ReHarga);
$totalRows_ReHarga = mysql_num_rows($ReHarga);
?>
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01
Transitional//EN" "http://www.w3.org/TR/html4/loose.dtd">
<html>
<head>
<title>Untitled Document</title>
<meta http-equiv="Content-Type" content="text/html;
charset=iso-8859-1">
<style type="text/css">
<!--
.style1 {
    font-family: Arial, Helvetica, sans-serif;
    font-weight: bold;
    color: #0000FF;
}
.style6 {color: #FFFFFF; font-family: Arial, Helvetica, sans-serif;
font-weight: bold;}
-->
</style>
</head>

<body>
<p class="style1">Form Isian Harga Perzona</p>
<form method="post" name="form1" action="<?php echo
$editFormAction; ?>">
    <table align="left" bgcolor="#0099FF">
        <tr valign="baseline">
            <td nowrap align="right"><span class="style6">Zona
Asal:</span></td>

```

```
<td><input type="text" name="zona_asal" value=""
size="32"></td>
</tr>
<tr valign="baseline">
<td nowrap align="right"><span class="style6">Zona
Tujuan:</span></td>
<td><input type="text" name="zona_tujuan" value=""
size="32"></td>
</tr>
<tr valign="baseline">
<td nowrap align="right"><span
class="style6">Harga:</span></td>
<td><input type="text" name="harga" value=""
size="32"></td>
</tr>
<tr valign="baseline">
<td nowrap align="right">&nbsp;</td>
<td><input type="submit" value="Simpan"></td>
</tr>
</table>
<input type="hidden" name="MM_insert" value="form1">
</form>
<p>&nbsp;</p>
</body>
</html>
<?php
mysql_free_result($ReHarga);
?>
```